**PAT-NO:** 

JP358185930A

**DOCUMENT-IDENTIFIER:** JP 58185930 A

TITLE:

**MOTORCYCLE** 

**PUBN-DATE:** 

October 29, 1983

## **INVENTOR-INFORMATION:**

**NAME** 

**COUNTRY** 

AOI, KAZUO NAKAO, YASUO NORIMATSU, NOBUO

## **ASSIGNEE-INFORMATION:**

NAME

**COUNTRY** 

YAMAHA MOTOR CO LTD N/A

**APPL-NO:** 

JP57067070

APPL-DATE: April 23, 1982

INT-CL (IPC):

F02B037/00, B60K013/02, B60K013/04

**US-CL-CURRENT:** 60/605.1

## **ABSTRACT:**

PURPOSE: To shorten lengthes of feed and exhaust pipes in a cross-flow type engine with a feed pipe and an exhaust pipe oppositely connected with a cylinder head between by arranging a turbo supercharger and an air cleaner behind the engine.

CONSTITUTION: In a cross-flow type parallel two-cylinder engine 50 in a motorcycle, a feed pipe 78(78a and 78b) in front of a cylinder head 56 and an exhaust manifold 58 in the rear are respectively arranged. At this stage, a turbo supercharger 60 is arranged sideways behind the engine 50, and the collected end of the exhaust manifold 58 to an exhaust inlet of its turbine 62 and a silencer 68 to an exhaust outlet via an exhaust pipe 66 are respectively connected. A suction pipe 74 connected to an air cleaner 70 is connected to a suction inlet of a compressor 64 of the supercharger 60, while a suction outlet is connected to the above-said feed pipe 78 via a feed pipe 80 and a feed box 76.

COPYRIGHT: (C)1983,JPO&Japio

第 3 図

